



PTFE SPACER

PTEF LINED FLANGED SPACER

PTEF LINED SPACER

	5	10	15	20	25	30	35	40	50	55	60	70	80	90	100	110	125	130	140	150	160	170	
20	A	A	B	B	B	B	B	B	B	B	B	C	C	C	-	-	-	-	-	-	-	-	
25	A	A	A	B	B	B	B	B	B	B	B	C	C	C	-	-	-	-	-	-	-	-	
32	A	A	A	A	B	B	B	B	B	B	B	B	C	C	C	-	-	-	-	-	-	-	
40	A	A	A	A	B	B	B	B	B	B	B	B	C	C	C	-	-	-	-	-	-	-	
50	A	A	A	A	B	B	B	B	B	B	B	B	B	C	C	C	-	-	-	-	-	-	
65	A	A	A	A	A	B	B	B	B	B	B	B	B	C	C	C	C	-	-	-	-	-	
SO	A	A	A	A	A	B	B	B	B	B	B	B	B	B	C	C	C	C	-	-	-	-	
90	A	A	A	A	A	B	B	B	B	B	B	B	B	B	C	C	C	C	-	-	-	-	
100	A	A	A	A	A	B	B	B	B	B	B	B	B	B	B	C	C	C	C	-	-	-	
125	A	A	A	A	A	A	B	B	B	B	B	B	B	B	B	C	C	C	C	-	-	-	
150	A	A	A	A	A	A	B	B	B	B	B	B	B	B	B	B	C	C	C	-	-	-	
200	A	A	A	A	A	A	B	B	B	B	B	B	B	B	B	B	C	C	C	-	-	-	
250	A	A	A	A	A	A	A	B	B	B	B	B	B	B	B	B	B	B	C	C	-	-	
300	A	A	A	A	A	A	A	A	B	B	B	B	B	B	B	B	B	B	B	B	C	C	
350	A	A	A	A	A	A	A	A	B	B	B	B	B	B	B	B	B	B	B	B	B	C	C

* VENT HOLE

SPECIFICATIONS :

- ALL DIMENSIONS ARE IN mm
- OTHER DIMENSIONS & SPECIFICATIONS ARE AS GIVEN IN PTFE LINED PIPE DRAWING
- MATERIAL CONSTRUCTION :

PIPE : ANSI B 36.10, ASTM A 106 Gr. B FLANGE : ANSI B 16.5, ASA 150#, IS 2062 Gr. A

LINER : PTFE, ASTM D 1457 TYPE III for LINED & FLANGED SPACERS / TYPE I FOR PTFE SPACERS

NOTE : THE LENGTH VALUES INDICATED ARE MINIMUM.